

## Z-3250

### Handy Wireless CCD Scanner



Designed for optimal reading performance, the compact Z-3250 offers wide scanning range and wireless communication technology for easy handling of any applications. Z-3250 includes a 32-bit CPU and excellent scan engine in a small yet powerful unit delivering intuitive and rapid scanning regardless of environment.

- Compact, light weight and portable
- Compatible with iOS/Android devices and Windows PC
- 32-bit microprocessor
- Captures barcodes on mobile phone, tablet, or computer screens

1. Portability and mobility
2. iOS compatible
3. Antimicrobial housing available for medical usage



#### OPERATIONAL

Light Source	617 nm visible red LED
Optical System	Linear CCD array
Microprocessor	32 bit
Depth of Field	4 mil: 50 – 90 mm      5 mil: 50 – 120 mm 7.5 mil: 30 – 210 mm    10 mil: 30 – 240 mm 13 mil: 30 – 330 mm    20 mil: 40 – 380 mm (Note : DOF may vary depending on environment condition and barcode quality.)
Scan Rate	330 scans per second
Min. Bar Width	4 mil
Print Contrast	30% @ UPC/EAN 100%
Indicator	Three-color LED ( green, red & blue )
Programmable Operation	Beeper tone & volume
System Interface	USB HID, Virtual COM, OPOS

#### PHYSICAL

Dimension	97.0 x 40.0 x 23.0 mm
Weight	79.7 g ( battery included )

#### POWER

Input Voltage	5 VDC ±10%
Battery	3.7V, 850 mAh, Li-ion rechargeable battery
Operating Current	Charging: 440 mA; non-charging: 150 mA
Battery Life	Over 80 hours at 6 scans per minute (depending on condition)

#### RADIO

##### COMMUNICATION

Radio Interface	RF wireless compatible with BT 2.1 SPP/HID profile mode
Working Range	Up to 100M ( depends on operating environment )

##### REGULATORY

EMC	CE & FCC DOC compliant, VCCI, BSMI
-----	------------------------------------

##### ENVIRONMENTAL

Operating Temperature	0°C ~ 50°C ( 32°F ~ 122°F )
Storage Temperature	-20°C ~ 60°C ( -4°F ~ 140°F )
Humidity	5% ~ 95% RH ( non-condensing )
Light Level	0 – 100,000 Lux ( fluorescence )
Drop Durability	Designed to withstand 1.2M drops
Environmental Sealing	IP43 rated sealing

##### DECODING CAPABILITY

1D Barcode

UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF 2 of 5, IATA Code, MSI, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, JAP, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, Telepen

